

VN-50/55/60-1

Non-Overcenter Aerial Lift

WORKING HEIGHT: Up to 60' 5"

HORIZONTAL REACH: Up to 36' 2"

PLATFORM CAPACITY: Up to 700 lbs.



The **VERSALIFT** product line has grown to encompass models for every market. Whether it be a 29' man lift or a 108' material handler, there is a **VERSALIFT** to get the job done.

For more information

Versalift
254.399.2100
www.VERSALIFT.com

VN-50/55/60-I



Non-Overcenter Aerial Lift

General Specifications (based on 40" frame)

VN-55

Horizontal Reach	36 ft. 2 in. (11 m)	<p>Models VN-50-I and VN-60-I also available. Please contact your distributor for specifications and information.</p>	
2-Man Platform Capacity	700 lbs. (318 kg)		
Lower Boom Lift Eye Capacity	1100 lbs. (500 kg)		
Upper Boom Articulation	175° articulation relative to lower boom		
Lower Boom Articulation	105° total articulation horizontal to 15° past vertical		
Platform Rotation	180°		
WITH STANDARD PEDESTAL			
Height to Bottom of Platform	55 ft. 5 in. (16.8 m)	<p>OPTIONS:</p> <ul style="list-style-type: none"> •Hydraulic Tilt Platform •One-Man End-Mount Platform •Platform Liner •Platform Cover •Lower Boom Lifting Eye Attachment • Two-Speed Manual Throttle Control •Emergency Power •Category B Dielectric Testing & Certification •Outrigger Boom Interlock System •Auxiliary Outriggers •Dual Hydraulic Tool Outlets •Flow-Sensing Throttle •Line-Lifting Socket •Unitrol H.R. 	
Working Height	60 ft. 5 in. (18.3 m)		
Stowed Travel Height	10 ft. 11 in. (3.2 m)		
Weight of Lift With Outriggers	6370 lbs. (2890 kg)		
HYDRAULIC SYSTEM			
Operating Pressure	2250 psi (158 kg/cm2)5°		
Flow Rate	8 gpm (30.2 lpm)		
Filtration Return	10 Micron Return		
Filtration Suction	100 Mesh Suction		
System Type	Closed and Open Center		
Power Source	PTO Pump		
INSULATION			
Upper Boom Insulation Gap (With or Without Test Bands)	239 in. (6.1 m)		
Lower Boom Insulation Gap	24 in. (0.6 m)		

NOTE:

1. Specifications may vary without prior notice
2. Required GVWR can vary significantly with chassis, lift mounting, location, service body, accessories and desired payload.