

# VST-5000/5500/6000-I

## Articulated/Telescopic Aerial Device

---

**BUCKET CAPACITY:** 750 lbs. (340 kg)

**WORKING HEIGHT:** Up to 65 ft. 1 in. (19.8 m)

**HORIZONTAL REACH:** Up to 38 ft. 9 in. (11.8 m)



The **VERSALIFT** product line has grown to encompass models for every market. Whether it be a 29' man lift or a 180' material handler, there is a **VERSALIFT** to get the job done.

### For more information

Versalift  
254.399.2100  
[www.VERSALIFT.com](http://www.VERSALIFT.com)

# VST-5000/5500/6000-I

Articulated/Telescopic Aerial Device



## General Specifications (based on 40" frame)

Horizontal Reach  
Maximum Platform Capacity  
Lower Boom Lift Eye Capacity

### VST-5000

36 ft. 8 in. (11.2 m)  
750 lbs. (340 kg)  
1000 lbs. (455 kg)

### VST-5500

37 ft. 11 in. (11.6 m)  
750 lbs. (340 kg)  
1000 lbs. (455 kg)

### VST-6000

38 ft. 9 in. (11.8 m)  
750 lbs. (340 kg)  
1000 lbs. (455 kg)

## STANDARD PEDESTAL

Bottom of Platform Height  
Working Height  
Stowed Travel Height  
Weight of Lift with Outriggers

49 ft. 8 in. (15.1 m)  
54 ft. 8 in. (16.7 m)  
11 ft. 11 in. (3.6 m)  
6,900 lbs. (3152 kg)

55 ft. 3 in. (16.8 m)  
60 ft. 3 in. (18.4 m)  
11 ft. 11 in. (3.6 m)  
9,180 lbs. (4164 kg)

60 ft. 1 in. (18.3 m)  
65 ft. 1 in. (19.8 m)  
11 ft. 11 in. (3.6 m)  
9,330 lbs. (4232 kg)

## HYDRAULIC SYSTEM

Operating Pressure  
Flow Rate  
Filtration  
  
System Type  
Power Source

2250psi (158 kg/cm2)  
7.5 gpm (28 lpm)  
10 micron return  
100 mesh suction  
  
Open Center  
PTO PUMP

2250psi (158 kg/cm2)  
7.5 gpm (28 lpm)  
10 micron return  
100 mesh suction  
  
Open Center  
PTO PUMP

2250psi (158 kg/cm2)  
7.5 gpm (28 lpm)  
10 micron return  
100 mesh suction  
  
Open Center  
PTO PUMP

## BOOM ARTICULATION

Outer/Inner Boom Articulation  
Inner Boom Extension  
Lower Boom Articulation

-25 to +85°  
141 in. (3.58 m)  
0° to +92°

-25 to +85°  
141 in. (3.58 m)  
0° to +92°

-25 to +85°  
141 in. (3.58 m)  
0° to +86°

## INSULATION GAPS

Upper Boom Fully Retracted  
Fully Extended  
Lower Boom

38 in. (1.0 m)  
172 in. (4.4 m)  
24 in. (0.61 m)

51 in. (1.3 m)  
185 in. (4.7 m)  
24 in. (0.61 m)

38 in. (1.0 m)  
179 in. (4.5 m)  
24 in. (0.61 m)

## W/MATERIAL HANDLING OPTION

Maximum Jib & Winch Capacity 1000 lbs. (455 kg)

### NOTE:

1. Specifications may vary without prior notice
2. Required GVWR can vary significantly with chassis, lift mounting, location, service body, accessories and desired payload.

### OPTIONS:

- Auxiliary Outriggers
- Second Set of Tool Power Ports
- Lifting Eye
- Taller Pedestals
- Back Up Pump
- Two-Speed Manual Throttle Control
- Material Handling Jib & Winch Hydraulic Extension and Articulation
- Jib Load Indicator
- TruGuard™